




453246 ISS T 10.08

NOTE: _____

Speed: **n=1450⁻¹ 50 Hz**
 Impeller: **Max. dia 175 mm**
 Min. dia 135 mm
 Pump inlet: **101,6 mm**
 Pump outlet: **76 mm**

Performance data refer to water at 20°C
 Permissible tolerance ±5%






453246 ISS T 10.08

NOTE: _____

Speed: $n=2900^{-1}$ 50 Hz
 Impeller: Max. dia 175 mm
 Min. dia 135 mm
 Pump inlet: 101,6 mm
 Pump outlet: 76 mm

Performance data refer to water at 20°C
 Permissible tolerance $\pm 5\%$






453246 ISS T 10.08

NOTE: _____

Speed: $n=1750^{-1}$ 60 Hz
 Impeller: Max. dia 175 mm
 Min. dia 135 mm
 Pump inlet: 101,6 mm
 Pump outlet: 76 mm

Performance data refer to water at 20°C
 Permissible tolerance $\pm 5\%$



453246 ISS T 10.08

NOTE: _____

Speed: $n=3500^{-1}$ 60 Hz
 Impeller: Max. dia 175 mm
 Min. dia 135 mm
 Pump inlet: 101,6 mm
 Pump outlet: 76 mm

Performance data refer to water at 20°C
 Permissible tolerance $\pm 5\%$

